

and second bodies, moving relative to the field device and thereby each coil side of the at least one air-core coil traversing the direction of movement, and is connected at an outer edge of the air gap with another coil side directly or via a predominantly inactive conductor or winding head conductor into at least one air-core coil, wherein the air gap, in section transverse to the direction of movement, comprises at least two neighboring air gap sections, each two of which abut one another with their air gap boundary surfaces belonging to the first body at the joint edge arising in this way, and each coil side of the at least one air-core coil runs through the air gap with its air gap sections, with each edge changing its geometric form and thereby completing a bend or fold around the first body and each coil side running essentially in the air gap and every coil side strokes across both pole surfaces during relative motion.

B1
(cont)

86. (NEW) An electrical machine according to claim 85, wherein the air gap, in section transverse to the direction of movement, is comprised of at least one curved air gap section, which is delimited by the inside of the first body and in which each coil side of the at least one air-core coil extends essentially along the full length of the curve, and the coil sides run through the air gap with its air gap sections.

87. (NEW) An electrical machine according to claim 86, wherein the air gap, in section transverse to the direction of movement, is comprised of at least one curved air gap section, which is delimited by the inside of the first body and in which each coil side of the at least one air-core coil extends essentially along the full length of the curve, and the coil sides run through the air gap with its air gap sections and essentially in the air gap, and the at least one air gap section is in the shape of a circular arc.

88. (NEW) An electrical machine according to claim 85, wherein, in section transverse to the direction of movement, the at least one curved air gap section is an irregular curve.

89. (NEW) An electrical machine according to claim 88, wherein, in section transverse to the direction of movement, the irregular curved air gap section is elliptical.

90. (NEW) An electrical machine according to claim 85, wherein the air-core coil is located essentially within the air gap.

91. (NEW) An electrical machine according to claim 85, wherein the air gap, which in section transverse to the direction of movement, comprises at least two neighboring air gap sections, are straight and lie at an angle to one another, whereby they intersect at one of their boundary surfaces, belonging to the first body.

92. (NEW) An electrical machine according to claim 85, wherein the air gap, in section transverse to the direction of movement, comprises at least two neighboring air gap sections which abut one another at a boundary surface which belongs to the first body, forming the edge, with one air gap section straight and one air gap section curved.

93. (NEW) An electrical machine according to claim 85, wherein, the air gap, in section transverse to the direction of movement, comprises at least two neighboring air gap sections which transition directly into one another.

94. (NEW) An electrical machine according to claim 85, wherein, in section transverse to the direction of movement, the air gap is assembled from three air gap sections, with two straight air gap sections lying in parallel connected through a third air gap section, which is either straight and lies at a 90° angle to each of them or is a curved air gap section.

95. (NEW) An electrical machine according to claim 85, wherein the air gap, in section transverse to the direction of movement, comprises at least two air gap sections lying in parallel, with the boundary surfaces.

96. (NEW) An electrical machine according to claim 85, wherein, in section transverse to direction of movement, the air gap comprises several abutting air gap sections, which are straight or curved, and through which each coil side of the at least one air-core coil runs, thereby completing at least one left bend and one right bend.

97. (NEW) An electrical machine according to claim 96, wherein thereby at least three straight air gap sections lie, in section transverse to the direction of movement, parallel to one another.

98. (NEW) An electrical machine according to claim 96, wherein the air gap, in section transverse to the direction of movement, comprises three straight air gap sections, with two air gap sections lying parallel to one another, and the third air gap section assuming an angle of 90° to them.

99. (NEW) An electrical machine according to claim 85, wherein a conductor of the air-core coil in the folded region in the region of the edge is also at least partially penetrated by the magnetic field, with the magnetic field not running from one air gap boundary surface to the other in essentially a straight line.

B1
(cont)

100. (NEW) An electrical machine according to claim 85, wherein, the air gap, in section transverse to the direction of movement, comprises at least two neighboring air gap sections which contain, in their boundary surfaces which belong to the first body and abut one another, magnetic partial poles which, out over the joint edge or with an outer edge, form a joint continuous pole which is magnetized orthogonally to its air gap boundary surface.

101. (NEW) An electrical machine according to claim 85, wherein, the air gap, in section transverse to the direction of movement, comprises at least two neighboring air gap sections, and the magnetic poles belong at least to different boundary surfaces of the air gap and the magnetic poles of the one air gap section, which belong to the boundary surface of the first body, lie with their faces at a distance to the return path material of the abutting, neighboring boundary surface of the other air gap section, which comprises at least predominantly return path material.

102. (NEW) An electrical machine according to claim 85, wherein, in section transverse to the direction of movement, the air gap comprises at least three air gap sections, with two straight air gap sections lying in parallel connected by a straight third air gap section, and magnetic poles belong to at least one of the two parallel boundary surfaces of the parallel air gap sections of the first body and are affixed to at least one of the sides of a slot-

shaped return path body belonging to the first body and the boundary surface of the air gap section, which connects the two edges, in which one boundary surface of the air gap section abuts one of each of the air gap sections, comprises return path material and forms a flat return path of the first body, which is a return path flat band, which lies at a distance to the faces of the magnetic poles and is connected with the return path body approximately in the middle or on one edge, and an air gap boundary surface of the air gap section, to which magnetic poles belong, lies opposite to the return path flat band.

103. (NEW) An electrical machine according to claim 85, wherein, in section transverse to the direction of movement, at least one second body in the folded region in the region of the edge at least partially follows the conductor or a curved coil trace at a uniform distance.

B1
Cont

104. (NEW) An electrical machine according to claim 85, wherein at least one second body is connected via its edges lying in the direction of movement with a return path flat band which delimits the air gap on one side in the folded region in the region of an edge.

105. (NEW) An electrical machine according to claim 85, wherein the return path flat band carries, on the side toward the air gap, magnetic poles which extend transverse to the direction of movement, alternate in the direction of movement, and are magnetized in the direction of the first body, in the direction of the edge.

106. (NEW) An electrical machine according to claim 85, wherein it is composed of several machines which use a joint second body of the field device.

107. (NEW) An electrical machine according to claim 85, wherein, in section transverse to the direction of movement, first and second bodies are securely connected directly or via a body, at the outer edges of the opposing boundary surfaces of the air gap, with the second body having at least one continuous slot in the direction of movement, for leading through an coil support, which divides the air gap boundary surface of the second body approximately in the middle in the direction of extension of the air gap and/or is located in a folded region of the at least one air-core coil.

108. (NEW) An electrical machine according to claim 85, wherein, in section transverse to the direction of movement, first and second bodies are securely connected directly or via a body, at the outer edges of the opposing boundary surfaces of the air gap, with the second body continuously delimiting the air gap opposite to the first body and the coil support connected at the other outer edge of the air gap with a winding head or an inactive conductor region of the at least one air-core coil and led out of the air gap region.

109. (NEW) An electrical machine according to claim 85, wherein the field device is surrounded by a housing or is itself the housing or part of the housing, and either the at least one air-core coil is securely connected with a shaft or axle, with the field device journaled directly and/or via a housing, or the at least one air-core coil is journaled directly and/or via a coil support and/or via a housing on the shaft or axle, and the field device is thereby securely connected with the shaft or axle.

110. (NEW) An electrical machine according to claim 85, wherein the movement is linear.

111. (NEW) An electrical machine according to claim 85, wherein the movement of the field device and the at least one air-core coil is rotational relative to an axle or a shaft.

112. (NEW) An electrical machine according to claim 85, wherein the field device, at least in the shape of at least three coaxial disk-shaped bodies lying at intervals, each as a disk or disk ring, is located on an axle or shaft with each one disk-shaped body located neighboring one second disk-shaped body, and these, in section transverse to the direction of movement, each delimiting one air gap section, whose boundary surfaces belonging to the first body abut at the outer edge of the first body, and magnetic poles belong to the second disk-shaped body on the side toward the air gap which are magnetized orthogonally to the air gap, extend in the direction of the axle, and alternate around the periphery, and at least one air-core coil, each coil side of which changes its geometric form at the outer edge, and which is bent or folded around the first body, with this being a very thin disk-shaped body, at least in its peripheral region, with boundary surfaces which predominantly comprise return path material, and each coil side on both sides of the first disk-shaped body extending into the air gap sections, approximately in the middle between each two disk-shaped bodies and at equal

distances from them, in the direction of the axle or shaft, and is connected in its region nearest the axle with another coil side into an air-core coil, with the first and second disk-shaped bodies rotatable uniformly with one another and relative to the at least one air-core coil.

113. (NEW) An electrical machine according to claim 85, wherein the field device, at least in the shape of at least three coaxial disk-shaped bodies lying at intervals, each as a disk or disk ring, is located on an axle or shaft, with each one disk-shaped body located neighboring one second disk-shaped body, and these, in section transverse to the direction of movement, each delimiting one air gap section, which each run on one side of the first disk-shaped body in the direction of the shaft or axle, and magnetic poles belong to at least one of the facing sides of the first and second disk-shaped bodies which are magnetized orthogonally to the air gap boundary surface, which extend in the direction of the axle, and which alternate around the periphery, with the first body comprising a slot-shaped return path body, which, in section transverse to the direction of movement, is very narrow, and magnetic poles which it carries on one of its sides, and the field device delimits a further air gap section in the peripheral region whose boundary surface belonging to the first body abuts each of the boundary surfaces also belonging to it of the neighboring air gap sections in each edge, and at least one air-core coil, with each coil side running at least partially through the air gap in the peripheral region and changing its geometric shape at both outer edges of the first body and bent or folded around the first body, extending outward from there on both sides of the first disk-shaped body in the direction of the axle or shaft, into each of the air gap sections approximately centrally between each two disk-shaped bodies at equal distances from them, and connected there with another coil side into an air-core coil, with the field device rotatable relative to at least one air-core coil and the first.

B1
Cont

114. (NEW) An electrical machine according to claim 85, wherein the field device is located, at least in the form of at least two coaxial nested drum-shaped bodies at a distance from one another, on an axle or shaft, with each one first drum-shaped body located neighboring one second drum-shaped body and these, in section transverse to the direction of movement, each delimiting one air gap section, with two straight air gap sections or at least one straight and one curved air gap section or at least one curved air gap section forming the air gap, which approaches the axle or shaft in at least one region, with each coil side of the at

least one air-core coil, during its course through the air gap in the direction of the axis or shaft, bent within at least one curved air gap section and/or changing its shape on at least one edge, at which each two neighboring air gap sections abut at their boundary surfaces belonging to the first body and bending or folding around the first body and extending over the entire air gap approximately centrally between the first and second body and at approximately equal distances from them, and the magnetic poles, which delimit the air gap and each air gap section on at least one side, are preferably magnetized orthogonally to their air gap boundary surface, extend along the air gap in section transverse to the direction of movement, and alternate around the periphery, and the field device rotates relative to the at least one air-core coil.

B1
lost

115. (NEW) An electrical machine according to claim 114, wherein the first drum-shaped body has the shape of a hollow or full circular cylinder and the second drum-shaped body has the shape of a hollow circular cylinder, with at least one of the facing shell sides of the first and second bodies, which delimit an air gap section, containing magnetic poles which are alternate around the periphery, and, in section transverse to the direction of movement, at least one of the facing sides of the first and second body, which delimits an air gap section, on the face on at least one side of the first body, containing magnetic poles, which alternate around the periphery, and the edge is formed by the abutting boundary surfaces of the shell and face sides of the air gap section belonging to the first body, each coil side of the at least one air-core coil is bent or folded around it and it extends from there outward into the air gap section on the shell side and in the direction of the axle or shaft in the air gap section on the face side.

116. (NEW) An electrical machine according to claim 115, wherein the first drum-shaped body has the shape of a hollow or full circular cylinder and the second drum-shaped body has the shape of a hollow circular cylinder, with at least one of the facing shell sides of the first and second bodies, which delimit an air gap section, containing magnetic poles which are radially magnetized and alternate around the periphery, and, in section transverse to the direction of movement, at least one of the facing faces of the first and second body, which delimit an air gap section on the face on at least one side of the first body, containing magnetic poles, which are magnetized orthogonally to the air gap boundary surface and axially and which alternate around the periphery, with the air gap sections, in section

transverse to the direction of movement, lying orthogonally to the air gap section, and the boundary surfaces, belonging to the first body, of one air gap section on the shell side and one air gap section on the face, each abutting in an edge of the first body, around which each coil side of the at least one air-core coil is bent or folded and extends from there into the air gap section on the shell side and into the air gap sections on the face, each in the direction of the axle or shaft.

B1
(cont)

117. (NEW) An electrical machine according to claim 114, wherein the first drum-shaped body has the shape of a hollow or full circular cylinder and the second drum-shaped body has the shape of a hollow circular cylinder, with at least one of the facing shell sides of the first and second bodies, which delimit an air gap section, containing magnetic poles, which are radially magnetized and alternate around the periphery, and the circular cylinder, in section transverse to the direction of movement, having faces slanted or bent inwards on at least one side toward an axle or shaft, with at least one of the facing faces of the first and second body, which delimits an air gap section on the face on at least one side of the first body, containing magnetic poles, which are magnetized orthogonally to the slanted or along the bending radius and which alternate around the periphery, and at least one edge formed by the abutting boundary surfaces belonging to the first body of the air gap sections on the shell side and face, in which each coil side of the at least one air-core coil changes its geometric shape and is bent or folded around the first body during its course through the air gap and extends into the air gap section on the shell side and into at least one air gap section on the face in the direction of the axle or shaft.

118. (NEW) An electrical machine according to claim 114, wherein the field device is in the form of at least three cylindrical bodies and the cylindrical body nearest the axle is a full or hollow cylinder and all further bodies are hollow cylinders and are nested in each other at a uniform interval at least on the shell side, with, in axial section, the boundary surfaces of one first body and one second body at a time delimiting one air gap section at a time, which each extend axially on the inner and outer shell surfaces of the first hollow cylinder, and at least one of the facing shell surfaces of the first and second cylindrical bodies has magnetic poles, which are extend axially, and alternate around the periphery, and preferably at least one of the facing faces of the first and second cylindrical bodies, which delimit an air gap section or a folded region on at least one side of the first body, also has

magnetic poles, which are extend in the direction of the axle or shaft, and alternate around the periphery, and each coil side of the at least one air-core coil is bent around at least one edge of a hollow cylindrical first body, which is formed by each two neighboring, abutting boundary surfaces of neighboring air gap sections, and extending from there outward on both sides of the edge, into an air gap section on the face or on one side at a time into an air gap section on the face in the direction of the axle or shaft and on the other side into an air gap section on the shell side.

119. (NEW) An electrical machine according to claim 85, wherein the field device comprises at least in the form of at least two long bodies, with each one first long body located neighboring one second long body, in section transverse to the direction of movement, and these each delimiting one air gap section, with two straight air gap sections or at least one straight and one curved air gap section or at least one curved air gap section forming the air gap, with each coil side of the at least one air-core coil bent in its course through the air gap around at least one first body within at least one curved air gap section and/or changing its geometric shape at least one edge of the long first body and bent or folded around the first body, and extending over the complete air gap approximately centrally between the first and second body and at approximately the same distance from each of them, and the magnetic poles, which delimit the air gap and each air gap section on at least one side, are magnetized orthogonally to their air gap boundary surface, extend, in section transverse to the direction of movement, along the air gap, and alternate around the periphery, and the field device moves linearly relative to at least one air-core coil.

120. (NEW) An electrical machine according to claim 119, wherein the long bodies are at least three long, plate-shaped bodies of a small, uniform thickness, which lie at uniform intervals from one another, with an air gap section located between each first plate-shaped body and second plate-shaped body, and the air gap sections lying parallel to one another in section transverse to the direction of movement, with the plate-shaped bodies being long relative to their width and the long sides lying in the direction of movement and magnetic poles belonging to at least one of the facing sides of the first and second plate-shaped bodies which extend transverse to the direction of movement and are magnetized orthogonally to the surface of the plate-shaped body delimiting the air gap, and the boundary surfaces belonging to the first body, which has, in section transverse to the direction of